

Control- and safety isolating transformer **STEU 630/24**



Picture shows STEU 160/23

Advantages

- Dual input voltage 230 and 400 Vac
- Reduced inrush current
- High power density due to a compact construction design
- Primary side ± 15 V taps for voltage adjustment
- Very good corrosion protection and low noise due to BLOCK IMPEX vacuum impregnation
- Fast installation because of the use of push-in terminals
- Contact protected screw connection terminals complying with UVV BGV A3
- Simple mounting due to robust metal footplate with oval slots
- DIN rail clamp included up to 250 VA


Applications

As a control transformer for the electrical isolation of the input and output sides. The construction of the transformer is designed to supply control systems according to EN 60204.

As an isolating transformer for the safe electrical isolation of the input and output sides. The transformer may be used to set up protective separation as a protective measure in accordance with VDE 0100.

As a safety transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Control transformer
to: VDE 0570 Teil 2-2, DIN EN 61558-2-2, EN 61558-2-2, IEC 61558-2-2,
UL 5085-1/-2, CSA 22.2 No.66
Safety isolating transformer
to: VDE 0570 Teil 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6, UL
5085-1/-2, CSA 22.2 No.66

Approvals





Control- and safety isolating transformer **STEU 630/24**

Electrical data

Type	STEU 630/24
Input	
Rated input voltage	230/400 Vac
Tappings Input	±15 V
Rated frequency	50 - 60 Hz
Output	
Rated output voltage	2 x 12 Vac
Rated power VDE (DB cos phi=1)	630 VA
Rated power VDE (KB cos phi=0.5)	2.350 VA
No-load voltage (app. x factor)	1.04
Efficiency	92 %
Standards	
Classification	Control- and safety isolating transformer
Approvals	
Approvals	cURus
Environment	
Ambient temperature max.	104.0 °F
Type of cooling	self-cooling
Safety and protection	
Type	Open type
Insulation class	VDE=B, UL=class 130
Protection index	IP 00
Safety class (prepared)	I
Short circuit strength	non-short-circuit proof
PRI Fusing recommendation by circuit breaker with tripping characteristic type 20 x I _{rated} related to set)	
Setting range 230 ±15 Vac	2.50 - 4.00 A
Setting value 230 ±15 Vac	3 A
Setting range 400 ±15 Vac	1.60 - 2.50 A
Setting value 400 ±15 Vac	1.7 A
Order numbers	
Order Number	STEU 630/24

Mechanical data

Type	STEU 630/24
Terminal and mounting	
Fixing method	Base plate
Fixing screws	M6
Terminals Input	push-in terminals, 4 mm ²
Terminals Output	push-in terminals, 4 mm ²
Connection type	Tab connector, 6.3 x 0.8 mm
Measures and weights	
Weight	17.42 lbs
Dimensions in inch	

Subject to change.