
Separating transformer

# CT-015-060-12-0




## Advantages

- Fused versions available
- Versions with DIN rail for additional components available
- 100 % finger-safe
- Jumpers included for primary voltage selection
- Very good corrosion protection and low noise thanks to BLOCK IMPEX vacuum impregnation
- Up to 2,500 VA

## Applications

As a control power transformer for adjustment of the voltage and simple electrical isolation.

## Sample application





## Standards

Separating transformer
to: EN 61558 part 1 with part 2-1, UL 5085-1/-2;2:2, CSA 22.2 No. 66

## Approvals

UL 5085-1/-2, CSA 22.2 No.66



# Separating transformer
# CT-015-060-12-0


## Electrical data

| Type | CT-015-060-12-0 |
|---|---|
| **Input** | |
| Rated input voltage | 600 Vac |
| Rated input current | 0.29 Aac |
| **Output** | |
| Rated output voltage | 120 Vac |
| Power | 150 VA |
| **Approvals** | |
| Approvals | cURus |
| **Environment** | |
| Ambient temperature | max. 104 °F |
| Type of cooling | Air natural |
| **Safety and protection** | |
| Type | Open type |
| Insulation class | B, class 130 |
| Protection index | IP 00 |
| Safety class (prepared) | I |
| Short circuit strength | non-short-circuit proof |
| **Order numbers** | |
| **Order Number** | **CT-015-060-12-0** |

## Mechanical data

| Type | CT-015-060-12-0 |
|---|---|
| **Terminal and mounting** | |
| Fixing method | Base plate |
| Terminals Input | Screw clamp, 4 mm² |
| Fixing screws | M4 |
| Terminals Output | Screw clamp, 4 mm² |
| Connection type | Tab connector, 6.3 x 0.8 mm |
| **Measures and weights** | |
| Weight | 4.85 lbs |

### Dimensions in inch




Subject to change.