Line reactor, three-phase

LR3 40-5/4



Picture shows LR3 40-4/63

Advantages

- Use as line reactor, commutating reactor or PFC reactor
- Ensuring the short-circuit voltage of 3, 4 or 5 % to the mains
- Power harmonic mitigation
- Starting current limitation
- Increases the service life of equipment
- Low ripple
- Bridging voltage dips
- Peak current limitation
- Very good corrosion protection and low noise due to vacuum impregnation
- Integrated lifting rings
- Multifunctional fixing rails

Applications

Line reactor to minimize mains pollution, to reduce the reactive-power components and charging currents in the DC link capacitor and to improve the cos(phi).

Standards

Line- and commutation reactor to
DIN EN 61558-2-20, IEC 61558-2-20, UL 506, CSA 22.2

Approvals

UL 506, CSA 22.2

BLOCK Transformatoren-Elektronik GmbH • Phone +49 4231 678-0 • info@block.eu

BLOCK
block.eu



Line reactor, three-phase
LR3 40-5/4


Electrical data

Type	LR3 40-5/4
Operating data	
Rated voltage	3 x 400 Vac
Rated voltage (IEC)	3 x 690 Vac
Rated voltage (UL)	3 x 600 Vac
Short circuit voltage uK	5 % @ 400 Vac
Voltage drop	11.6 Vac
Rated current	3 x 4 A
Rated frequency	50 - 60 Hz
Inductance	9.2 mH
Inductance deviation	±10%
Output	
Power loss	13.9 W
Approvals	
Approvals	cURus
Environment	
Ambient temperature	14 °F to +104 °F
Type of cooling	AN
Safety and protection	
Type	Open type
Insulation class	IEC=B, UL=class 130
Protection index	IP 00
Safety class (prepared)	I
Test voltage	4000 Vac
Order numbers	
Order Number	**LR3 40-5/4**

Mechanical data

Type	LR3 40-5/4
Terminal and mounting	
Terminals phase	Screw clamp, 4 mm²
Connection type	Tab connector, 6.3 x 0.8 mm
Fixing method	Fixing rail
Fixing screws	M4
Measures and weights	
Weight	2.89 lbs

Dimensions in inch



Subject to change.