

Line reactor, three-phase **LR3 48-3/115**



Picture shows LR3 40-4/63

Advantages

Use as line reactor, commutating reactor or PFC reactor
Ensuring the short-circuit voltage of 3 - 5 % to the mains
Power harmonic mitigation
Starting current limitation
Increases the service life of equipment
Low ripple
Bridging voltage dips
Peak current limitation
Very good corrosion protection and low noise due to vacuum impregnation
Integrated lifting rings
Multifunctional fixing rails

Applications

Line reactor to minimize mains pollution, to reduce the reactive-power components and charging currents in the DC link capacitor and to improve the cos(phi).

Standards

Safety isolating transformer
to: VDE 0570 Part 2-6, DIN EN 61558-2-6, EN 61558-2-6, IEC 61558-2-6,
UL 5085-1/-2, CSA 22.2 No.66

Approvals



UL 506, CSA 22.2



Line reactor, three-phase LR3 48-3/115

Type		LR3 48-3/115
Electrical data	Operating data	
	Rated voltage	max. 3 x 480 Vac
	Short circuit voltage uK	3 % @ 480 Vac
	Voltage drop	8.3 Vac
	Rated current	115 A
	Rated frequency	50 - 60 Hz
	Inductance	0.193 mH
	Inductance deviation	±10%
	Approvals	
	Approvals	cURus, cULus
	Environment	
	Ambient temperature	14 °F to +104 °F
Type of cooling	AN	
Safety and protection		
Type	Open type	
Insulation class	IEC=F, UL=class 155	
Protection index	IP 00	
Safety class (prepared)	I	
Test voltage	4000 Vac	
Order numbers		
Order Number	LR3 48-3/115	

Type		LR3 48-3/115
Mechanical data	Terminal and mounting	
	Terminals phase	Flat copper
	Connection type	for M8
	Fixing method	Fixing rail
	Fixing screws	M8
Measures and weights		
Weight	46.96 lbs	

Dimensions in inch

