
Line reactor, three-phase

LR3 48-3/630



Picture shows LR3 40-4/63

Advantages

- Use as line reactor, commutating reactor or PFC reactor
- Ensuring the short-circuit voltage of 3 - 5 % to the mains
- Power harmonic mitigation
- Starting current limitation
- Increases the service life of equipment
- Low ripple
- Bridging voltage dips
- Peak current limitation
- Very good corrosion protection and low noise due to vacuum impregnation
- Integrated lifting rings
- Multifunctional fixing rails

Applications

Line reactor to minimize mains pollution, to reduce the reactive-power components and charging currents in the DC link capacitor and to improve the cos(phi).

Standards

Line- and commutation reactor to
DIN EN 61558-2-20, IEC 61558-2-20, UL 506, CSA 22.2

Approvals

UL 506, CSA 22.2



Line reactor, three-phase
LR3 48-3/630


Electrical data

Type	LR3 48-3/630
Operating data	
Rated voltage	max. 3 x 480 Vac
Short circuit voltage uK	3 % @ 480 Vac
Voltage drop	8.3 Vac
Rated current	630 A
Rated frequency	50 - 60 Hz
Inductance	0.035 mH
Inductance deviation	±10%
Approvals	
Approvals	cURus, cULus
Environment	
Ambient temperature	14 °F to +104 °F
Type of cooling	AN
Safety and protection	
Type	Open type
Insulation class	IEC=H, UL=class 180
Protection index	IP 00
Safety class (prepared)	I
Test voltage	4000 Vac
Order numbers	
Order Number	**LR3 48-3/630**

Mechanical data

Type	LR3 48-3/630
Terminal and mounting	
Terminals phase	Flat copper
Connection type	for M8
Fixing method	Fixing rail
Fixing screws	M8
Measures and weights	
Weight	154.76 lbs

Dimensions in inch



Subject to change.